



ZONE II®

SPECIAL FEATURES:

- Straight back, rubber coated temple tips.
- Soft nose pad and temples provide a comfortable fit.
- Built in nose pads elevate frame for precision fit and weightless wear.
- Lenses filter 99% of harmful UV rays.

GENERAL SPECIFICATIONS

Lens Thickness:	2.4mm	PD	68 mm
Lens Base	9.5 curve	Weight	32 gm
Lens size vertical	43.5mm	Lens Size Diagonal	64 mm
Bridge	9.0mm	Temple length (lens-tip)	160.5mm

Overall Width (hinge-hinge)	136.5mm
Closest point between lens	18.6mm
Closest point between temple tips	87.0mm

FRAME AND LENS OPTIONS:

Frame colors:	Various
Lens options:	Standard Color, tinted, or mirror lens available

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	full eye protection 9.5 curve lens
Frame	Nylon 6.6	dual lens frame w/ side protection
Side Shield	n/a	n/a
Nose piece	PVC	Universal, integral to frame
Temple Tip	PVC	Slip on the temple
Temple	Polycarbonate	Spatula with soft tip end
Hinge	Nylon/Polycarbonate	3 barrel type, integral to frame/temple
Screw	Stainless Steel standard hinge screw	

MARKINGS:

PACKAGING:

STANDARDS:

MEETS ANSI Z87.1 STANDARDS

TEST RESULTS AVAILABLE UPON REQUEST